

## • FLOW / PRESSURE / VOLUME

---

**Pmax**.....: 350 bar  
**Qmax**.....: 320 l/min @ 60 Hz  
 ( 265 l/min @ 50 Hz )

## • MOTOR / ENGINE

---

**Type**.....: ATB, IP56, EEx de, ATEX  
 : ATB BD 250M-4, IP56, EEx de, ATEX  
 : WEG 250S/M, IP56, EEx de, ATEX

- 400V (D), 55 kW, 1470 rpm, 95 A, 50 Hz
- 690V (Y), 55 kW, 1475 rpm, 55 A, 50 Hz
- 440-480V (D), 63 kW, 1770 rpm, 100-92 A, 60 Hz
- 660-690V (Y), 63 kW, 1770 rpm, 59-56 A, 60 Hz
- 400V (D), 63 kW, 1770 rpm, 97 A, 60 Hz

## • PUMP

---

**Pump Type**.....: PARKER PV180  
 : KAWASAKI 3KVL

- 180CCM
- 200CCM

## • CONNECTIONS

---

Pressure.....: 3/4" Tema  
 Leak oil.....: 1/2" Tema  
 Return.....: 1" Tema

## • START CABINET

---

Apply Oil & Gas Electro

- EEx de IIC T6
- 400V – 440V – 480V – 660V – 690V



## • DIMENSIONS

---

Length.....: 2300 (mm)  
 Width.....: 1300 (mm)  
 Height.....: 1950 (mm)

**Weight**.....: 2200 (kg)

## • CAPACITY

---

**Tank:** 500 Liters

- Built in radiator for hydraulic cooling

## • LIFTING

---

**DNV 2.7-1** Lift slings

## • ADDITIONAL INFORMATION

---

*Other configurations on request*