

• FLOW / PRESSURE / VOLUME

Pmax.....: 350 bar
Qmax.....: 320 l/min @ 60 Hz
 (265 l/min @ 50 Hz)

• MOTOR / ENGINE

Type.....: ATB, IP56, EEx de, ATEX
 : ATB BD 250M-4, IP56, EEx de, ATEX
 : WEG 250S/M, IP56, EEx de, ATEX

- 400V (D), 55 kW, 1470 rpm, 95 A, 50 Hz
- 690V (Y), 55 kW, 1475 rpm, 55 A, 50 Hz
- 440-480V (D), 63 kW, 1770 rpm, 100-92 A, 60 Hz
- 660-690V (Y), 63 kW, 1770 rpm, 59-56 A, 60 Hz
- 400V (D), 63 kW, 1770 rpm, 97 A, 60 Hz

• PUMP

Pump Type.....: PARKER PV180
 : KAWASAKI 3KVL

- 180CCM
- 200CCM

• CONNECTIONS

Pressure.....: 3/4" Tema
 Leak oil.....: 1/2" Tema
 Return.....: 1" Tema

• START CABINET

Apply Oil & Gas Electro

- EEx de IIC T6
- 400V – 440V – 480V – 660V – 690V



• DIMENSIONS

Length.....: 2300 (mm)
 Width.....: 1300 (mm)
 Height.....: 1950 (mm)

Weight.....: 2200 (kg)

• CAPACITY

Tank: 500 Liters

- Built in radiator for hydraulic cooling

• LIFTING

DNV 2.7-1 Lift slings

• ADDITIONAL INFORMATION

Other configurations on request